



FEATURES

- Cast iron agitator creates a powerful stirring motion to allow pumping of silt, slurry and solids
- Hardened impeller resists abrasion and wear to ensure long life in aggressive situations
- HDPE encapsulated body, stainless steel water jacket and polymer power cable resist corrosive environments
- Smooth pump body does not require wheels or other devices to install the G1275 pump
- 5 HP motor to provide the torque required for pumping silt, slurry and solid contaminants

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product









Cyan Park, Unit 3 Jimmy Hill Way, Coventry CV2 4QP, UK







TYPICAL SENSOR PERFORMANCE SPECIFICATIONS

dese Dimensions: in. (mm) desight: lbs. (kg) dese Materials dese Materials design Specifications design des design de	34" x 13.2" (80 115 (53) SUS-304 90 feet (23 n 250 gpm (92 104 F (40 C) 5 HP (3.7 kw 3600 RPM Outlet: 3 in. I 0.5" (12 mm)	meters) 45 lpm) /) I.D. (80 mm)					
ase Materials ump Specifications aximum head aximum flow aximum liquid temperature ump Power otor speed tting Size(s) olids capacity MP PERFORMANCE HEAD 80	90 feet (23 n 250 gpm (92 104 F (40 C) 5 HP (3.7 kw 3600 RPM Outlet: 3 in. I	45 lpm) /) I.D. (80 mm)					
aximum head aximum flow aximum liquid temperature ump Power otor speed tting Size(s) blids capacity MP PERFORMANCE HEAD 80 60	90 feet (23 n 250 gpm (92 104 F (40 C) 5 HP (3.7 kw 3600 RPM Outlet: 3 in. I	45 lpm) /) I.D. (80 mm)				· os/	
aximum head aximum flow aximum liquid temperature ump Power otor speed tting Size(s) blids capacity MP PERFORMANCE HEAD 80 60	250 gpm (92 104 F (40 C) 5 HP (3.7 kw 3600 RPM Outlet: 3 in. I	45 lpm) /) I.D. (80 mm)				•	
aximum flow aximum liquid temperature ump Power otor speed tting Size(s) olids capacity MP PERFORMANCE HEAD 80	250 gpm (92 104 F (40 C) 5 HP (3.7 kw 3600 RPM Outlet: 3 in. I	45 lpm) /) I.D. (80 mm)					
aximum liquid temperature ump Power otor speed tting Size(s) blids capacity MP PERFORMANCE HEAD 80 60	104 F (40 C) 5 HP (3.7 kw 3600 RPM Outlet: 3 in. I	(I.D. (80 mm)				· os/	
ump Power otor speed tting Size(s) plids capacity MP PERFORMANCE HEAD 80	5 HP (3.7 kw 3600 RPM Outlet: 3 in. I	I.D. (80 mm)				0	0
otor speed tting Size(s) olids capacity MP PERFORMANCE HEAD 80	3600 RPM Outlet: 3 in. I	I.D. (80 mm)					-01
tting Size(s) plids capacity MP PERFORMANCE HEAD 80	Outlet: 3 in. I						
MP PERFORMANCE HEAD 80			and the same of th				
MP PERFORMANCE HEAD 80	0.5" (12 mm))					4/3/4/2
HEAD							
60							
1		EF	F				ш
40							出
40						1	%
						A	
20						-1	
						//	
						\	
0 50	100		150	200	-2	250	300
		CAPAC	CITY GPM			-30	300
5							
4							
2							

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

200





0



100



150


CAPACITY GPM



Cyan Park, Unit 3 Jimmy Hill Way, Coventry CV2 4QP, UK

250





300